




| | | | | | | | |
|--------------------------------------|--------------|----------------|----------------|----------------|----------------|----------------|----------------|
| Wymiar: | <6 | >6-30 | >30-120 | >120-400 | >400-1000 | >1000-2000 | >2000-4000 |
| Odchyłka: | +0.1 -0.1 | +0.2 -0.2 | +0.3 -0.3 | +0.5 -0.5 | +0.8 -0.8 | +1.2 -1.2 | +2.0 -2.0 |
| Wymiar krótszego boku: | | | | | | | |
| Odchyłka [minuty]: | +0.0 -0.0 | +0.50 -0.50 | +1.20 -1.20 | +1.20 -1.20 | +1.20 -1.20 | +1.20 -1.20 | +1.20 -1.20 |
| Odchyłka [mm na 100 mm]: | +1.6 -1.6 | +0.9 -0.9 | +0.6 -0.6 | +0.6 -0.6 | +0.6 -0.6 | +0.6 -0.6 | +0.6 -0.6 |
| Tolerancje ogólne wg DIN 7168 mittel | | | | | | | |



| | | | | | | |
|--------------------------------|-------------------|----------------|--------------------|------------------------|--|---|
| Kod: P2012 P | | | | Nazwa: Spinka | | Capricorn Spółka z o.o. Ciemna 12 58-160 Świebodzin tel. +48 74 854 05 16 fax +48 74 854 05 83 |
| Materiał: Polipropylen HP 500J | | | | Podzespół: | | |
| Nazwisko | | Data | | Produkt: | | |
| Rys.: | Roman Szponar | 2009-09-16 | | | | |
| Spr.: | | | | | | |
| Zatr.: | | | | | | |
| Podz.: | Format: A4 | Rys.: 1 | Masa: 2.5 g | Nr rys.: SRM.03 | spinka.par spinka.DKJ.dft | |