



1. GENERAL DESCRIPTION

Anti-corrosion protection – without silicone.

2. FEATURES

- Thanks to its low surface tension, **ECOPROTECT FG** repels humidity on metal surfaces. It lays down a high quality damp-proof film, that assures a long-lasting efficient protection.
- Registered NSF N°... H2
- 360° valve allows to use the product upside down.

3. APPLICATIONS

- Protection of parts machine-finished with emulsions or water-based solutions.
- Protection of parts degreased with alkaline detergents and rinsed with water.
- Protection against corrosion of metallic moulds or parts stored outdoors, under shelter.

4. DIRECTIONS

A safety data sheet (MSDS) according to EU directive 91/155/EEC and amendments is available for all CRC products.

5. TYPICAL PRODUCT DATA (without propellant)

- High covering power.
- Transparent film.
- Neutralises fingerprints.
- Good lubricant, avoiding cleaning of moving parts before use or activation.
- Chemically inert for alloys and non-ferrous metals (such as zinc, aluminium, copper, Zamak, ...).

6. PACKAGING

Aerosol: 12 x 500 ml

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com. We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.

Version : 50606 03 0607 00
Date : 27 June 2007



Manufactured by :
CRC Industries Europe BVBA
Touwslagerstraat 1 – 9240 Zele – Belgium
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34
www.crcind.com

