



CRC DIESEL CLEAN PLUS ANTI SMOKE

Ref. : 10763 (cars) - 10764 (trucks)

1. GENERAL DESCRIPTION

A concentrated fuel detergent combined with a special iron based anti-smoke additive, with a wide action range, based on surface active agents, solvents and deposit modifiers. These special ingredients all have specific functions to eliminate fuel system problems, injector deposits, water contaminated fuel sludge build-up and smoke.

2. FEATURES

- Cleans the entire fuel distribution and atomization system.
- Reduces significantly black smoke emissions.
- Improves combustion.
- Stabilises fuel injection.
- Optimizes fuel economy.
- Reduces typical "fouled injector" problems like rough idling, frequent stalling at idle, loss of power.
- Prevents valve sticking, leading to improved drive ability, smooth idling and increased acceleration power.
- Increases the oxidation stability of the fuel promoting the resistance to sediment formation.
- Regular use will keep them clean during extended mileage.
- Protects fuel distribution system from rust and corrosion.

3. APPLICATIONS

- Single port fuel injectors
- Multi port fuel injectors
- Cars
- Busses
- Trucks
- Tractors

4. DIRECTIONS

- Clean up: **Cars:** 1 bottle for 50 – 70 l fuel.
Trucks: 1 bottle (concentrated formula) for 400 – 500 l fuel.
Pour 1 bottle of product into a full fuel tank and drive at least 100 km before passing the emissions test.
- Keep clean: Pour 1 bottle of product into a full fuel tank every 3.000 km-5000 km (cars) or every 20000-25000 km (trucks).
- A safety data sheet (MSDS) according EU directive 93/112 is available for all CRC products.



Manufactured by :
CRC Industries Europe BVBA
Touwslagerstraat 1 – 9240 Zele – Belgium
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34
www.crcind.com





CRC DIESEL CLEAN PLUS ANTI SMOKE

Ref. : 10763 (cars) - 10764 (trucks)

5. TYPICAL PRODUCT DATA (without propellant)

	Formula	normal (cars)	concentrated (trucks)
Appearance	:	amber liquid	amber liquid
Odour	:	typical	typical
Specific gravity @ 20°C	:	0,81	0,90
Pour point	:	< -30°	< -30°
Flash point	:	62°C	62°C
Dynamic viscosity @ 40°C	:	2,5 Cps	20 Cps

6. PACKAGING

Bottle: 12 x 250 ml

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com.

We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.

Version : 10763 (cars) - 10764 (trucks) 03 0501 04

Date : 30 March 2010



Manufactured by :
CRC Industries Europe BVBA
Touwslagerstraat 1 – 9240 Zele – Belgium
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34
www.crcind.com

