




Bobcat®

Flail Cutter

Attachments



Standard features

- Variable-speed displacement motor allows the flail cutter to be "tuned in" to your machine, depending on its hydraulic capacity. By varying the motor displacement to accept auxiliary hydraulic flows ranging from 64 to 151 l/min, the flail cutter can be operated on many different carriers.
- Floating linkage is standard on the flail cutter. This, along with the attachment's compact deck length, lets the unit follow the contour of the land regardless of the pitch or attitude of the carrier, permitting the cutter up to ten degrees of oscillation.
- Safety compliance The flail cutter complies with the SAE J1001 standard for industrial flail mowers. It is standard-equipped with an automatic shut-off device which allows approximately ten inches of vertical travel in the Bob-Tach™; mounting system before the flail cutter shuts down.
- Full-width tapered rear roller provides greater turning ability during operation.
- Adjustable rear hatch allows operators to vary the size of discharged material, ranging from small, for mulching applications to coarse for high-performance cutting.

Applications

- Municipal jobs
- Forestry
- Parks
- Landscaping
- Nurseries
- Hobby farmers

	Item number	Compatible with loader
Flail cutter FC155	7115498	S130, S150, S160, S175, S175H, S185, S185H, S205, S205H, T140, T190, T190H
Flail cutter FC175	7108385	S175, S175H, S185, S185H, S205, S205H, S220, S220H, S250, S250H, S300, S330, S300H, S330H, T190, T190H, T250, T250H, T300, T320, T300H, T320H, A300, A300H
Flail cutter FC200	7101894	S175, S175H, S185, S185H, S205, S205H, S220, S220H, S250, S250H, S300, S330, S300H, S330H, T190, T190H, T250, T250H, T300, T320, T300H, T320H, A300, A300H

Weights and dimensions

	Operating weight (kg)	Shipping weight (kg)	Overall Width (C) (mm)	Overall Height (B) (mm)	Overall Length (A) (mm)
Flail cutter FC155	580	580	1856	683	1457
Flail cutter FC175	696	696	2056	683	1457
Flail cutter FC200	746	746	2306	683	1457

Characteristics and performance

	Flow (gpm)	Max Drum speed (rpm)	Shut off float height (mm)
Flail cutter FC155	64 – 151	2200	254
Flail cutter FC175	64 – 151	2200	254
Flail cutter FC200	64 – 151	2200	254

