

TRIPLE GAS ANALYZER INCLUDING CARBON MONOXIDE

PAC CHECK® Model 333

CO, CO₂ & O₂ Accuracy in a Free Standing, Portable Headspace Analyzer



The PAC CHECK® Model 333 is a handheld Carbon Monoxide, Carbon Dioxide, and Oxygen analyzer for checking modified atmospheres inside packages. It is the ideal instrument for portable, fast and accurate headspace tests on the packaging line, in warehouses or in laboratories.



- Portable
- Accurate results
- Easy-to-use & Read

Benefits

- Long-lasting batteries for a full day's work. Take up to 500 samples on one full charge.
- Rugged protective boot to prevent damage when dropped.
- Simple and accurate 1, 2, or 3-point calibration.
- Instruments holds up to 240 tests and can be downloaded to your computer via our Data Grab™ software.

mocon®

ERMEC

Equipos de control de calidad

Tel.: (+34) 902 450 160


Fax: (+34) 902 433 088

ermec@ermec.net

www.ermec.net

Typical applications where portability would be effective.

- **Modified Atmosphere Packaging in Meat Packaging**



Data Grab™ Software Option Software is available to organize and save the data from the Model 333.



Specifications

Range of CO Sensor	0.02% - 2%
Accuracy - CO Sensor	±0.2% CO abs or ±5% relative reading, whichever is greater
CO Measurement Method	Chemical Cell
Range - O ₂ Sensor	0 - 100%
Accuracy - O ₂ Sensor	±0.1% abs or 2% relative reading, whichever is greater
Oxygen Measurement Method	Chemical Cell
Accuracy of CO ₂ Sensor	2% abs @ 0 - 20%; 3% abs @ 20 -100%
Carbon Dioxide Measurement Method	Infrared
Response (CO)	Typical response time less than 30 seconds*
Response (O ₂ or CO ₂)	98% of final value within 7 seconds
Resolution (O ₂ or CO or CO ₂)	0.01%
Calibration (O ₂ or CO or CO ₂)	1, 2 or 3-point calibration
Sample Method	Auto internal sampling pump
Adjustable Pump Time	1 - 90 sec.
Barometric Pressure Range	400 - 760 mmHg
Display	128 x 68 LCD
Ambient Operating Temperature	5 - 40 C (0 to 45 C storage)
Ambient Humidity	10 to 90% non-condensing
Supply Voltage	100 -240 VAC or (8) 2000 mAh NiMH rechargeable batteries
Supply Frequency	50/60 Hz (includes battery recharger)
Languages	English

*95% of full scale step change in less than 60 seconds

mocon®

7500 Boone Ave. North
Minneapolis, MN 55428
USA
763-493-6370
www.mocon.com

For complete specifications for your application, please call.

MOCON and PAC CHECK are registered trademarks, and
DATA GRAB is trademark of MOCON.
PC333/806

Made in USA



Equipos de control de calidad

Tel.: (+34) 902 450 160
Fax: (+34) 902 433 088
ermec@ermec.net
www.ermec.net