
Data sheet

valid from: 8/2/22





AQUASYSTEM Stable Pipe PP-R PN25 SDR6

Attention:

- Aluminium foil is at close to the external surface of the pipe.
- Aluminium layer of the pipe must be peeled by a sharpener before welding procedure.

DN (mm)	Code	SP	PN (bar)	SDR	d (mm)	e (mm)	e1 (mm)	LB (mm)
20	**4102002000121**	100	25	6	20	4.5	0.15	4000
25	**4102002500221**	80	25	6	25	5.3	0.15	4000
32	**4102003200321**	40	25	6	32	6.5	0.15	4000
40	**4102004000421**	40	25	6	40	7.8	0.15	4000
50	**4102005000521**	20	25	6	50	9.4	0.15	4000
63	**4102006300621**	16	25	6	63	11.6	0.15	4000
75	**4102007500721**	12	25	6	75	13.6	0.15	4000
90	**4102009000821**	8	25	6	90	16.1	0.15	4000
110	**4102011007421**	4	25	6	110	19.4	0.15	4000

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland
Phone +41 -(0)52-631 1111
e-mail: info.ps@georgfischer.com
Internet: http://www.gfps.com