



JRG LegioStop JRGUSIT Combi distribution fitting gunmetal

- Temperature: max. 90°C
- Material: gunmetal, stainless steel, EPDM, plastic
- Factory setting: 600 kPa (6 bar)
- Connection: inlet female thread, outlet male thread
- Consisting of: stop valve, check valve closable, safety valve, heating charging valve, 2 drain valves, 3 test and closing plugs fitted, cap, non-rising handwheels

DN (mm)	Size (inch)	DN-DN-DN (mm)	JRG Code	GF Code	SP	Weight (kg)
25	1	25 - 25 - 25	5191.400	355 643 181	1	2.860
32	1 ¼	32 - 25 - 25	5191.480	355 643 183	1	2.900

DN (mm)	d1 G (inch)	d2 G (inch)	d3 G (inch)	d4 Rp (inch)	d5 Rp (inch)	d6 G (inch)	d7 TR 30 x 1.5	d8 G (inch)	d9 (mm)	d10 (mm)	d12 (mm)	h (mm)	l1 (mm)	l2 (mm)
25	1 ¼	1 ¼	¾	¾	¾	1	TR 30 x 1.5	½	60	53	53	77	364	8
32	1 ½	1 ¼	¾	¾	¾	1	TR 30 x 1.5	½	60	53	53	77	365	9

DN (mm)	l3 (mm)	l4 (mm)	l5 (mm)	z (mm)
25	43	145	130	17
32	44	145	130	17

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>