



## JRGARANT safety valve gunmetal

- Material: gunmetal
- Factory setting: available between 100 - 1000 kPa (1 - 10 bar)
- Connection: inlet male thread, outlet female thread

DN (mm)	GN (inch)	Size (inch)	JRG Code	GF Code	SP	Weight (kg)
15	½	½	1028.240	350 599 944	1	0.400
20	¾	¾	1028.320	350 599 945	1	0.684
25	1	1	1028.400	350 599 946	1	0.684

DN (mm)	GN (inch)	d1 R (inch)	d2 Rp (inch)	h1 (mm)	h2 (mm)	l1 (mm)	l2 (mm)	PN (bar)	Temperature (°C)	z (mm)
15	½	½	½	28	81	38	38	10	90	15
20	¾	¾	¾	32	81	41	68	10	90	17
25	1	1	1	39	85	46	69	10	90	22

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>