



JRG bypass mixing valve gunmetal

- Temperature: max. 65°C (short-term 90°C)
- Material: gunmetal, stainless steel, POM, EPDM, plastic
- Connection: male thread
- Consisting of: bypass, shut-off, fixed adjustable raw water admixture, back flow preventer, connection piece

GN (inch)	DN (mm)	JRG Code	GF Code	SP	Weight (kg)
1	25	5195.400	350 691 020	1	3.180
1 ¼	32	5195.480	350 691 021	1	3.490

GN (inch)	DN (mm)	d1 R (inch)	d2 G (inch)	d3 G (inch)	d4 G (inch)	d5 Rp (inch)	h1 (mm)	h2 (mm)	h3 (mm)	l1 (mm)	l2 (mm)	l3 (mm)	l4 (mm)	z (mm)	□
1	25	1	1 ¼	1	½	¼	10	35	105	168	115	75	34	50	6
1 ¼	32	1 ¼	1 ¼	1	½	¼	10	35	105	196	115	75	38	60	6

GN (inch)	DN (mm)	○
1	25	5
1 ¼	32	5

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>