



JRG bypass mixing valve gunmetal

- Temperature: max. 65°C (short-term 90°C)
- Material: gunmetal, stainless steel, POM, EPDM, plastic
- Connection: male thread
- Consisting of: bypass, shut-off, fixed adjustable raw water admixture, back flow preventer, connection piece

GN (inch)	DN (mm)	JRG Code	GF Code	SP	Weight (kg)
1 1/2	40	5195.560	350 691 022	1	7.770
2	50	5195.640	350 691 023	1	8.690

GN (inch)	DN (mm)	d1 R (inch)	d2 G (inch)	d3 G (inch)	d4 G (inch)	d5 Rp (inch)	d6 G (inch)	h1 (mm)	h2 (mm)	h3 (mm)	l1 (mm)	l2 (mm)	l3 (mm)	l4 (mm)	z (mm)
1 1/2	40	1 1/2	1 1/2	1 1/2	1/2	1/4	1 1/4	16	46	130	223	180	110	39	73
2	50	2	1 1/2	1 1/2	1/2	1/4	1 1/4	16	46	130	269	180	110	47	88

GN (inch)	DN (mm)	□	◇
1 1/2	40	6	6
2	50	6	6

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>