



JRG LegioStop distributor battery complete gunmetal

- Temperature: max. 30°C
- Material: gunmetal, stainless steel, EPDM, plastic
- Factory setting: PRV 400 kPa (4 bar) adjustment range 200 - 600 kPa (2 - 6 bar), safety valve 600 kPa (6 bar)
- Connection: male thread
- Consisting of: JRGUSIT NG battery valve 5151, JRGURED 1303, JRGUSIT Combi distribution fitting 5191

DN (mm)	Size (inch)	DN-DN-DN-DN (mm)	JRG Code	GF Code	SP	Weight (kg)
25	1	25-20-25-25	1511.400	355 623 518	1	5.870
32	1 ¼	32-20-25-25	1511.480	355 623 528	1	6.045

d1 G (inch)	d2 G (inch)	d3 G (inch)	d4 Rp (inch)	d5 Rp (inch)	d6 Rp (inch)	d7 G (inch)	d8 G (inch)	d9 G (inch)	d10 TR 30 x 1.5	h1 (mm)	h2 (mm)	h3 (mm)	l (mm)
1 ¼	1	1 ¼	¾	¾	¾	¾	1	½	TR 30 x 1.5	55	77	52	586
1 ½	1	1 ¼	¾	¾	¾	¾	1	½	TR 30 x 1.5	56	77	64	618

l1 (mm)	l2 (mm)	l3 (mm)	l4 (mm)	l5 (mm)	l6 (mm)	PN (bar)
37	133	93	145	130	48	16
42	149	104	145	130	48	16

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>