



## JRG LegioStop distributor battery complete gunmetal

- Temperature: max. 30°C
- Material: gunmetal, stainless steel, EPDM, plastic
- Factory setting: PRV 400 kPa (4 bar) adjustment range 200 - 600 kPa (2 - 6 bar), safety valve 600 kPa (6 bar)
- Connection: male thread
- Consisting of: JRGUSIT NG battery valve 5151.200, JRGURED Combi 1353.032, sleeve screw connection 350332105, connector/adaptor 9695.480, JRGUSIT Combi distribution fitting 5191

| DN<br>(mm) | Size<br>(inch) | DN-DN-DN-DN<br>(mm) | JRG<br>Code | GF<br>Code  | SP | Weight<br>(kg) |
|------------|----------------|---------------------|-------------|-------------|----|----------------|
| 32         | 1 ¼            | 32-20-25-25         | 1531.480    | 355 623 568 | 1  | 9.700          |

| DN<br>(mm) | Size<br>(inch) | DN-DN-DN-DN<br>(mm) | d1 G<br>(inch) | d2 G<br>(inch) | d3 G<br>(inch) | d4 G<br>(inch) | d5 Rp<br>(inch) | d6 Rp<br>(inch) | d7 G<br>(inch) | d8 G<br>(inch) | d9 G<br>(inch) | d10<br>TR 30 x 1.5 |
|------------|----------------|---------------------|----------------|----------------|----------------|----------------|-----------------|-----------------|----------------|----------------|----------------|--------------------|
| 32         | 1 ¼            | 32-20-25-25         | 1 ½            | 1              | 1 ¼            | ¾              | ¾               | ¾               | ¾              | 1              | ½              |                    |

| DN<br>(mm) | Size<br>(inch) | DN-DN-DN-DN<br>(mm) | h1<br>(mm) | h2<br>(mm) | h3<br>(mm) | h4<br>(mm) | l<br>(mm) | l1<br>(mm) | l2<br>(mm) | l3<br>(mm) | l4<br>(mm) | l5<br>(mm) | l6<br>(mm) | PN<br>(bar) |
|------------|----------------|---------------------|------------|------------|------------|------------|-----------|------------|------------|------------|------------|------------|------------|-------------|
| 32         | 1 ¼            | 32-20-25-25         | 56         | 77         | 393        | 120        | 897       | 42         | 149        | 383        | 145        | 130        | 48         | 16          |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>