



JRG LegioStop distributor battery complete gunmetal

- Temperature: max. 30°C
- Material: gunmetal, stainless steel, EPDM, plastic
- Factory setting: PRV 400 kPa (4 bar) adjustment range 200 - 600 kPa (2 - 6 bar), safety valve 600 kPa (6 bar)
- Connection: male thread
- Consisting of: JRGUSIT NG battery valve 5151, JRG CleanLine Combi 1371, JRGUSIT Combi distribution fitting 5191

DN (mm)	Size (inch)	DN-DN-DN-DN (mm)	JRG Code	GF Code	SP	Weight (kg)
25	1	25-20-25-25	1542.400	355 623 573	1	6.600
32	1 ¼	32-20-25-25	1542.480	355 623 583	1	7.920

DN (mm)	Size (inch)	DN-DN-DN-DN (mm)	d1 G (inch)	d2 G (inch)	d3 G (inch)	d4 G (inch)	d5 Rp (inch)	d6 Rp (inch)	d7 G (inch)	d8 G (inch)	d9 G (inch)	d10 (inch)
25	1	25-20-25-25	1 ¼	1	1 ¼	¾	¾	¾	¾	1	½	TR 30 - 1.5
32	1 ¼	32-20-25-25	1 ½	1	1 ¼	¾	¾	¾	¾	1	½	TR 30 - 1.5

DN (mm)	Size (inch)	DN-DN-DN-DN (mm)	h1 (mm)	h2 (mm)	h3 (mm)	h4 (mm)	l (mm)	l1 (mm)	l2 (mm)	l3 (mm)	l4 (mm)	l5 (mm)	l6 (mm)	PN (bar)
25	1	25-20-25-25	55	77	221	110	599	37	134	105	145	130	48	16
32	1 ¼	32-20-25-25	56	77	224	120	634	42	150	120	145	130	48	16

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>