



## JUNIOR safety group gunmetal chromium-plated

- Temperature: max. 90°C
- Material: gunmetal, stainless steel, EPDM, plastic
- Factory setting: pressure reducing valve 400 kPa (4 bar), safety valve 600 kPa (6 bar)
- Connection: female thread, male thread
- Consisting of: coarse filter, pressure reducing valve, safety valve, back flow preventer, unions

DN (mm)	GN (inch)	Size (inch)	JRG Code	GF Code	SP	Weight (kg)
15	½	½	<b>2230.241</b>	<b>350 712 984</b>	1	1.110
20	¾	¾	<b>2230.321</b>	<b>350 713 084</b>	1	1.480

DN (mm)	GN (inch)	Size (inch)	d R (inch)	d2 Rp (inch)	d3 G (inch)	d4 (mm)	d5 Rp (inch)	h1 (mm)	h2 (mm)	l (mm)	l1 (mm)	l2 (mm)	l3 (mm)	PN (bar)	z1 (mm)
15	½	½	1/2	¾	¾	30	¼	83	34	165	86	29	25	16	102
20	¾	¾	3/4	1	1	30	¼	87	40	182	95	30	29	16	113

DN (mm)	GN (inch)	Size (inch)	z2 (mm)
15	½	½	46
20	¾	¾	49

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>