



JUNIOR safety group gunmetal

- Temperature: max. 90°C
- Material: gunmetal, stainless steel, EPDM, plastic
- Factory setting: pressure reducing valve 400 kPa (4 bar), safety valve 600 kPa (6 bar)
- Connection: male thread
- Consisting of: coarse filter, pressure reducing valve, safety valve, back flow preventer, unions, pipe interrupter

GN (inch)	Size (inch)	DN (mm)	JRG Code	GF Code	SP	Weight (kg)
1/2	1/2	15	2240.240	350 712 983	1	1.300
3/4	3/4	20	2240.320	350 713 083	1	1.770

GN	d1 R	d2 R	d3 G	d4	d5 Rp	d6 G	h1	h2	h3	l	l1	l2	PN	z1	z2
(inch)	(inch)	(inch)	(inch)	(mm)	(inch)	(inch)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(bar)	(mm)	(mm)
1/2	1/2	3/4	3/4	30	1/4	1	83	71	29	165	86	25	16	102	46
3/4	3/4	1	1	30	1/4	1 1/4	87	80	34	182	95	30	16	113	49

GN	z3
(inch)	(mm)
1/2	90
3/4	103

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>