



JRG Sanipex MT Ball valve gunmetal

- Material: gunmetal, plastic
- Temperature: max. -20°C / +95°C (water, compressed air, vacuum)
- Connection: cone grip unions

d (mm)	DN (mm)	JRG Code	GF Code	SP	Weight (kg)	d1 (mm)	h (mm)	l (mm)	l1 (mm)	z1 (mm)	z2 (mm)	PN (bar)
16	12	6041.016	351 616 310	1	0.230	16	45	94	84	28	28	10
20	15	6041.020	351 620 310	1	0.308	20	49	109	84	31	31	10
26	20	6041.026	351 626 310	1	0.543	26	63	131	125	37	37	10
32	25	6041.032	351 632 310	1	0.933	32	71	158	125	42	42	10
40	32	6041.040	351 640 310	1	1.547	40	75	186	125	49	49	10

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>