



JRG bypass mixing valve gunmetal DN40/50

- Temperature: max. 65°C (short-term 90°C)
- Material: gunmetal, stainless steel, POM, EPDM, plastic
- Connection: male thread
- Consisting of: bypass, shut-off, fixed adjustable and volume-controlled raw water admixture, back flow preventer, connection piece

GN (inch)	DN (mm)	JRG Code	GF Code	SP	Weight (kg)
1 ½	40	5195.040	351 114 983	1	7.300
2	50	5195.050	351 114 993	1	7.700

GN (inch)	DN (mm)	d1 G (inch)	d2 G (inch)	d3 G (inch)	d4 G (inch)	d5 Rp (inch)	d6 G (inch)	h1 (mm)	h2 (mm)	h3 (mm)	l1 (mm)	l2 (mm)	l3 (mm)	□	PN (bar)
1 ½	40	1 ¼	1 ½	1 ½	½	¼	1 ¼	16	30	130	145	180	110	6	16
2	50	2 ¾	1 ½	1 ½	½	¼	1 ¼	16	30	130	175	180	110	6	16

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>