



Filtro JRG CleanLine Combi, PN 16 - 4 bar

- Temperatura: max. 30°C
- Material: bronce, acero inoxidable, EPDM, plástico
- Factory setting: 400 kPa (4 bar)
- Secondary pressure: 200 - 600 kPa (2 - 6 bar)
- Conexión: rosca macho
- Consisting of: combined pressure reducing valve, back flush fine filter

DN (mm)	Pulgadas (inch)	JRG Código	GF Código	SP	Peso (kg)
25	1	1370.025	350 690 932	1	2,580
32	1 ¼	1370.032	350 690 933	1	2,940

DN (mm)	d2 G (inch)	d3 Rp (inch)	d4 (mm)	h1 (mm)	h2 (mm)	l1 (mm)	l2 (mm)	l3 (mm)	PN (bar)	⊘	μm
25	1 ¼	¼	99	221	110	100	125	60	16	6	100
32	1 ½	¼	99	224	120	120	125	60	16	6	100

Los datos técnicos no son vinculantes. No constituyen expresamente características o propiedades garantizadas. Son susceptibles de modificación. En caso de duda se aplican nuestras Condiciones Generales de Venta

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>