



## JRG Safety set gunmetal

- Temperature: max. 90°C
- Material: gunmetal, stainless steel, EPDM, plastic
- Factory setting: 600 kPa (6 bar)
- Connection: male thread
- Consisting of: non-return valve, safety valve

| DN<br>(mm) | Size<br>(inch) | JRG<br>Code     | GF<br>Code         | SP | Weight<br>(kg) |
|------------|----------------|-----------------|--------------------|----|----------------|
| 20         | ¾              | <b>1631.020</b> | <b>351 061 181</b> | 1  | 0.739          |
| 25         | 1              | <b>1631.025</b> | <b>351 061 183</b> | 1  | 1.050          |
| 32         | 1 ¼            | <b>1631.032</b> | <b>351 061 185</b> | 1  | 1.280          |

| DN<br>(mm) | d1 G<br>(inch) | d2 Rp<br>(inch) | d3 G<br>(inch) | d4 Rp<br>(inch) | h2<br>(mm) | h3<br>(mm) | h4<br>(mm) | h5<br>(mm) | l1<br>(mm) | l2<br>(mm) | l3<br>(mm) | PN<br>(bar) | z1<br>(mm) | z2<br>(mm) | z3<br>(mm) |
|------------|----------------|-----------------|----------------|-----------------|------------|------------|------------|------------|------------|------------|------------|-------------|------------|------------|------------|
| 20         | 1              | ¾               | ¾              | ¼               | 7          | 32         | 62         | 37         | 56         | 77         | 48         | 10          | 24         | 63         | 17         |
| 25         | 1 ¼            | ¾               | 1              | ¼               | 7          | 32         | 62         | 49         | 68         | 82         | 48         | 10          | 25         | 75         | 17         |
| 32         | 1 ½            | ¾               | 1 ¼            | ¼               | 9          | 32         | 82         | 57         | 80         | 87         | 48         | 10          | 30         | 89         | 17         |

| DN<br>(mm) | Ø |
|------------|---|
| 20         | 6 |
| 25         | 6 |
| 32         | 6 |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>