



JRG Safety group gunmetal

- Temperature: max. 90°C
- Material: gunmetal, EPDM, plastic
- Factory setting: 600 kPa (6 bar)
- Connection: male thread
- Consisting of: non return valve, safety valve, unions, pipe interrupter

DN (mm)	GN (inch)	Size (inch)	JRG Code	GF Code	SP	Weight (kg)
15	½	½	2210.240	350 782 283	1	0.750
20	¾	¾	2210.320	350 782 383	1	1.200

DN (mm)	GN (inch)	d1 R (inch)	d2 R (inch)	d3 G (inch)	d4 (mm)	d5 Rp (inch)	d6 G (inch)	h1 (mm)	h2 (mm)	h3 (mm)	l (mm)	l1 (mm)	l2 (mm)	l3 (mm)	PN (bar)
15	½	½	1	¾	30	¼	1	83	75	29	130	45	35	25	10
20	¾	¾	1	1	30	¼	1 ¼	87	87	34	144	52	35	29	10

DN (mm)	GN (inch)	z1 (mm)	z2 (mm)	z3 (mm)
15	½	61	52	94
20	¾	70	54	110

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>