



DANFOSS Solenoid valve brass

- Material: brass, EPDM
- Connection: female thread
- Consisting of: plug, servo-controlled, 230 V coil, unplugged, pilot filter, slow-close
- Note: Minimum back pressure must be observed (approx. 0.5 bar)

GN (inch)	DN (mm)	JRG Code	GF Code	SP	Weight (kg)
½	15	6410.240	355 631 905	1	0.935
¾	20	6410.320	355 631 906	1	1.124
1	25	6410.400	355 631 907	1	1.570
1 ¼	32	6410.480	355 631 908	1	2.258
1 ½	40	6410.560	355 631 909	1	3.200
2	50	6410.640	355 631 910	1	5.124

GN (inch)	DN (mm)	d1 Rp (inch)	h (mm)	h1 (mm)	l (mm)	l1 (mm)	b (mm)	PN (bar)	Type
½	15	½	94	15	52	80	52	10	EV220 B15
¾	20	¾	98	18	52	90	58	10	EV220 B20
1	25	1	108	22	52	109	70	10	EV220 B25
1 ¼	32	1 ¼	115	27	52	120	82	10	EV220 B32
1 ½	40	1 ½	124	32	52	130	95	10	EV220 B40
2	50	2	130	37	52	162	113	10	EV220 B50

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>