



JRG Safety set gunmetal

- Temperature: max. 90°C
- Material: gunmetal, stainless steel, EPDM, plastic
- Factory setting: 600 kPa (6 bar)
- Connection: female thread
- Consisting of: non-return valve closable, safety valve

GN (inch)	DN (mm)	Size (inch)	JRG Code	GF Code	SP	Weight (kg)
3/4	20	3/4	1630.320	351 061 281	1	0.730
1	25	1	1630.400	351 061 283	1	1.030
1 1/4	32	1 1/4	1630.480	351 061 285	1	1.290

GN (inch)	DN (mm)	d1 Rp (inch)	d2 Rp (inch)	d3 G (inch)	d4 Rp (inch)	h1 (mm)	h2 (mm)	h3 (mm)	h4 (mm)	l1 (mm)	l2 (mm)	l3 (mm)	PN (bar)	z1 (mm)	z2 (mm)
3/4	20	3/4	3/4	3/4	1/4	75	8	32	62	56	77	48	10	12	33
1	25	1	3/4	1	1/4	90	10	32	62	68	82	48	10	15	40
1 1/4	32	1 1/4	3/4	1 1/4	1/4	110	9	32	62	80	87	48	10	19	52

GN (inch)	DN (mm)	z3 (mm)	⊙
3/4	20	17	6
1	25	17	6
1 1/4	32	17	6

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>