



JRGURED Válvula reductora de presión con uniones, PN25 - 4 bar

- Temperature: max. 70°C (short-term 90°C)
- Material: bronce, acero inoxidable, EPDM, plástico
- Factory setting: 300 kPa (3 bar), adjustment range 250 - 450 kPa (2.5 - 4.5 bar)
- Conexión: Rosca Hembra
- Consisting of: strainer 1'000 µm

GN	Pulgadas	DN	JRG	GF	SP	Peso
(inch)	(inch)	(mm)	Código	Código		(kg)
¾	¾	20	1380.320	350 739 001	1	1,480

GN	d1 Rp	d2	d3	h1	h2	h3	h4	l1	l2	PN	z	O1	O2	O3	O4
(inch)	(inch)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(bar)	(mm)				
¾	¾	66	80	22	78	64 - 154	23	110	22	16	41	32	36	10	6

Los datos técnicos no son vinculantes. No constituyen expresamente características o propiedades garantizadas. Son susceptibles de modificación. En caso de duda se aplican nuestras Condiciones Generales de Venta

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>