


JRG LegioStop JRGUSIT NG distribution valve gunmetal



- Temperature: max. 90°C
- Material: gunmetal, stainless steel, EPDM, plastic
- Connection: stem female thread, outlet male thread
- Spare upper part: see 5158

DN (mm)	Size (inch)	DN-DN (mm)	JRG Code	GF Code	SP	Weight (kg)
25	1	25-20	5151.100	350 835 220	1	0.750
25	1	25-25	5151.110	350 835 320	1	0.900
32	1 ¼	32-20	5151.200	350 835 420	1	0.850
32	1 ¼	32-25	5151.210	350 835 520	1	1.000
32	1 ¼	32-32	5151.220	350 835 620	1	1.150
40	1 ½	40-20	5151.300	350 835 720	1	0.950
40	1 ½	40-25	5151.310	350 835 820	1	1.100
40	1 ½	40-32	5151.320	350 835 920	1	1.250
40	1 ½	40-40	5151.330	350 836 020	1	1.500

d1 G (inch)	d2 G (inch)	d3 G (inch)	d4 G (inch)	d5 Rp (inch)	d6 (mm)	h1 (mm)	h2 (mm)	h3 (mm)	l1 (mm)	l2 (mm)	l3 (mm)	l4 (mm)	PN (bar)	z (mm)	⊙
1 ¼	1 ¼	1	¾	¾	53	85	55	7	128	37	8	8	16	83	6
1 ¼	1 ¼	1 ¼	1	¾	60	87	55	8	128	37	8	8	16	83	6
1 ½	1 ½	1	¾	¾	53	85	56	7	139	42	9	9	16	89	6
1 ½	1 ½	1 ¼	1	¾	60	87	56	8	139	42	9	9	16	89	6
1 ½	1 ½	1 ½	1 ¼	¾	70	91	56	9	139	42	9	9	16	89	6
1 ¾	1 ¾	1	¾	¾	53	85	57	7	150	45	10	10	16	96	6
1 ¾	1 ¾	1 ¼	1	¾	60	87	57	8	150	45	10	10	16	96	6
1 ¾	1 ¾	1 ½	1 ¼	¾	70	91	57	9	150	45	10	10	16	96	6
1 ¾	1 ¾	1 ¾	1 ½	¾	90	97	57	10	150	45	10	10	16	96	6

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>