



JRG Needle valve gunmetal For fine adjustments

- Temperature: max. 90°C (water, oil, petrol)
- Material: gunmetal, stainless steel, metal (plastic coated)
- Connection: female thread

DN (mm)	Thread Type	Size (inch)	JRG Code	GF Code	SP	Weight (kg)
8	GN	¼	6335.080	355 635 544	1	0.280
10	GN	⅜	6335.160	355 635 545	1	0.257
15	GN	½	6335.240	355 635 546	1	0.470
20	GN	¾	6335.320	355 635 547	1	0.496
25	GN	1	6335.400	355 635 548	1	0.970

DN (mm)	d1 (inch)	Rp (inch)	d2 G (inch)	d4 (mm)	h (mm)	l (mm)	z (mm)	PN (bar)
8	¼	¼	¼	50	100	45	13	16
10	⅜	⅜	⅜	50	100	45	13	16
15	½	½	½	60	81	60	17	16
20	¾	¾	¾	70	92	75	23	16
25	1	1	1	80	110	90	28	16

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>