



JRGUMAT Thermostatic mixing valve gunmetal Adjustment with hexagonal

- Material: gunmetal
- Factory setting: 18 / 26 / 38 / 42 / 50 / 55 / 60 / 65°C (adjustable)
- Connection: male thread

DN (mm)	Thread Type	Size (inch)	range (°C)	Temperature (°C)	JRG Code	GF Code	SP	Weight (kg)
15	GN	½	12 - 25	18	3100.018	350 281 425	1	1.030
15	GN	½	22 - 30	26	3100.026	350 281 426	1	1.030
15	GN	½	36 - 40	38	3100.038	350 281 423	1	1.030
15	GN	½	40 - 44	42	3100.042	350 281 422	1	1.030
15	GN	½	50 - 65	50	3100.050	350 281 421	1	1.030
15	GN	½	50 - 65	55	3100.055	350 281 427	1	1.045
15	GN	½	50 - 65	60	3100.060	350 281 428	1	1.030
15	GN	½	50 - 65	65	3100.065	350 281 409	1	1.030

DN (mm)	d1 R (inch)	d2 R (inch)	d3 G (inch)	h (mm)	h1 (mm)	h2 (mm)	h3 (mm)	l (mm)	l1 (mm)	l2 (mm)	l3 (mm)	l4 (mm)	l5 (mm)	l6 (mm)	PN (bar)
15	½	½	¾	75	50	25	60	168	50	29	26	30	16	72	10
15	½	½	¾	75	50	25	60	168	50	29	26	30	16	72	10
15	½	½	¾	75	50	25	60	168	50	29	26	30	16	72	10
15	½	½	¾	75	50	25	60	168	50	29	26	30	16	72	10
15	½	½	¾	75	50	25	60	168	50	29	26	30	16	72	10
15	½	½	¾	75	50	25	60	168	50	29	26	30	16	72	10
15	½	½	¾	75	50	25	60	168	50	29	26	30	16	72	10
15	½	½	¾	75	50	25	60	168	50	29	26	30	16	72	10

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>