



JRGUMAT Thermostatic mixing valve gunmetal Adjustment by hand

- Factory setting: 18 / 26 / 38 / 42 / 50°C (adjustable)
- Material: gunmetal
- Connection: male thread

DN (mm)	Thread Type	Size (inch)	range (°C)	Temperature (°C)	JRG Code	GF Code	SP	Weight (kg)
15	GN	½	12 - 25	18	3110.018	350 281 805	1	1.150
15	GN	½	22 - 30	26	3110.026	350 281 806	1	1.150
15	GN	½	36 - 40	38	3110.038	350 281 803	1	1.150
15	GN	½	40 - 44	42	3110.042	350 281 802	1	1.150
15	GN	½	50 - 65	50	3110.050	350 281 801	1	1.150
15	GN	½	50 - 65	55	3110.055	350 281 807	1	1.150
15	GN	½	50 - 65	60	3110.060	350 281 808	1	1.150

DN (mm)	Thread Type	Size (inch)	d1 R (inch)	d2 R (inch)	d3 G (inch)	h (mm)	h1 (mm)	h2 (mm)	h3 (mm)	l (mm)	l1 (mm)	l2 (mm)	l3 (mm)	l4 (mm)
15	GN	½	½	½	¾	75	50	25	60	168	50	29	47	30
15	GN	½	½	½	¾	75	50	25	60	168	50	29	47	30
15	GN	½	½	½	¾	75	50	25	60	168	50	29	47	30
15	GN	½	½	½	¾	75	50	25	60	168	50	29	47	30
15	GN	½	½	½	¾	75	50	25	60	168	50	29	47	30
15	GN	½	½	½	¾	75	50	25	60	168	50	29	47	30

DN (mm)	Thread Type	Size (inch)	l5 (mm)	l6 (mm)	PN (bar)
15	GN	½	16	93	10
15	GN	½	16	93	10
15	GN	½	16	93	10
15	GN	½	16	93	10
15	GN	½	16	93	10
15	GN	½	16	93	10
15	GN	½	16	93	10

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>